

Duette Unik RD 25 mm



ARTICLE CHARACTERISTICS



Material Composition

100% Pes



Weight in gr/m²

250



Anti Static

☒



Cutting direction



FabricWidth

4450



Flame Retardant

☐



Suitable For Humid Environment

☒



Pattern Repeat Width cm



Thickness in mm

0.15



Light Fastness

6-7



Anti Bacterial

☐



Pattern Repeat Height cm

TRANSPARENCY



Transparent

☐



Semi-transparent

☐



Opaque

☐



Room Darkening

☒

CLEANING



Hand

☐



Sponge

☒



Brush

☐

ENVIRONMENTAL LABELS



Oeko-tex

☐



GreenGuard

☐



Halogen free

☒



HD Keen On Green Bottle

☐



Cradle To Cradle

☐



PVC free

☒



HD Keen On Green Leaf

☐

Duette Unik RD 25 mm



LIGHT AND ENERGY VALUES

	A	B	D
Glass (mm)	4	4/12/4	4/16/4
U-value [W/(M²K)]	5.80	2.90	1.10
g-value[-]	0.85	0.76	0.32
$G=1/(1/U+1/G2)[W/(MK)]^2$	4.86	2.64	1.06

VALUES ACCORDING TO EN 410 / EN 13363-1 / EN 14501 (%)

Dessin	Rv	TV Total	TV Diff	TV Dir	Rs	Ts	Tuv	G	G _a	G _b	G _d	U _a	U _b	U _c
0628	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
3404	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
3405	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
3414	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
4206	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
4207	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
7887	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
7889	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
7891	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
7893	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
9245	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
9246	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
9247	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8
9249	77	0			72	0	0		29.4	32.7	24.4	2.1	1.6	0.8

EN 14501

Comfort value (Fc)	Glare control	Openness factor
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		
56.66		